

24-PLAIT MATT

THEATRE & EVENTS • UTILITIES • WINCHING

Traditional rope developed with modern manufacturing processes.

Reference	Diameter (mm)	Reel Length (m)	Weight (kg/100m)	Breaking Load (kg)		000/ White	452/ Buff	960/ Red	900/ Black	910/ Blue
1406	6	100	2.8	600		14060100000	-	-	-	-
1408	8	100	5.0	1,120		14080100000	14080100452	14080100960	14080100900	14080100910
1410	10	100	7.2	1,980		14100100000	14100100452	14100100960	14100100900	14100100910
1412	12	100	10.4	2,300		14120100000	14120100452	14120100960	14120100900	14120100910
1414	14	100	12.4	3,500		14140100000	-	14140100960	14140100900	14140100910
1416	16	100	17.0	5,430		14160100000	-	14160100960	14160100900	14160100910

The spun polyester increases grip while remaining soft.

FEATURES & BENEFITS

- 24-plait cover with 12-strand core
- Spun polyester used on outer
- Heat set and pre-stretched
- Full colour range available
- Softer to the touch for hand use
- Higher levels of grip
- Easily identified through colours

TYPICAL APPLICATIONS

- Sheets for yachting
- Theatrical applications

TECHNICAL INFORMATION

	Core	Cover
Construction	12-strand	24-plait
Material	Polyester	Polyester
Specific gravity	1.38	1.38
Resistance to acid	Yes	Yes
Resistance to alkali	Yes	Yes
Resistance to UV	Yes	Yes
Resistance to heat	^230°C	^230°C
Extension at break	25%	