

3-STRAND PRE-STRETCHED

LEISURE MARINE • COMMERCIAL MARINE • THEATRE & EVENTS • DEFENCE

A high performance line which is popular with classic yacht enthusiasts looking for a rope of exceptional quality combined with that classic look.

Reference	Diameter (mm)	Reel Length (m)	Weight (kg/100m)	Breaking Load (kg)	000/ White	994/ Beige
4403	3	300	1.0	310	44030300000	-
4404	4	100/300	1.4	500	44040300000	-
4405	5	100/300	1.7	670	44050300000	-
4406	6	100/300	3.0	1,050	44060300000	44060300994
4408	8	100/300	5.4	1,730	44080300000	44080300994
4410	10	200	8.0	2,640	44100200000	44100200994
4412	12	100/200	12.3	3,490	44120100000	44120100994
4414	14	100	16.5	4,200	44140100000	44140100994
4416	16	100	19.0	5,700	44160100000	44160100994
4418	18*	100	24.0	7,000	-	44180100994
4420	20*	100	30.0	8,000	-	44200100994
4424	24*	100	42.0	10,500	-	44240100994

Uniquely available in beige, the pre-stretched 3 strand offers a high performance rope for classic yacht rigging. The standard 3 strand specification is modified to ensure that the rope remains well balanced yet with a hard lay. English Braids 3 strand pre-stretched polyester rope is a cable laid rope of premium quality. This is a rope that exceeds the requirements of British standards and is a performance product with low stretch and superb stability. The rope is post lay heat treated under tension for reduced extension and to relieve stresses in laying up. This makes for a performance rope with less inclination to hockle or kink, yet retaining splicing ease.

TECHNICAL INFORMATION

	Core	Cover
Material	Polyester	
Specific Gravity	1.38	
Resistance to Acid	Yes	
Resistance to Alkali	Yes	
Resistance to UV	Yes	
Resistance to Heat	^230 C	

FEATURES & BENEFITS

- 3-strand spun polyester rope
- Softer to the touch than standard polyester
- Torque balanced
- Heat set in production process
- Traditional look and feel
- Anti-kinking rope in use

TYPICAL APPLICATIONS

- Halyard
- Luff line
- Lifting
- General winching