

8-STRAND NYLON ANCHORBRAID

LEISURE MARINE • COMMERCIAL MARINE

A traditional rope, manufactured to deliver maximum load extension characteristics

Reference	Diameter (mm)	Reel Length (m)	Weight (/100m)	Breaking Load (kg)	000/ White	900/ Black
2710	10	200	6.5	2,850	27100200000	27100200900
2712	12	200	9.3	3,760	27120200000	27120200900
2714	14	100	11.5	4,390	27140100000	27140100900
2716	16	100	17.5	6,500	27160100000	27160100900
2718	18	100	21.0	7,400	27180100000	27180100900
2720	20	100	26.0	9,700	27200100000	27200100900
2724	24	220 (Coils)	37.3	14,370	27240220000	-
2728	28	220 (Coils)	51.0	18,500	27280220000	-
2732	32	220 (Coils)	66.40	23,930	27320220000	-

The 8-strand nylon rope provides optimal extension both from the construction and the base material making it ideal for jobs where shock loading is a factor.

TECHNICAL INFORMATION

	Core
Construction	8-strand
Material	Nylon
Specific Gravity	1.19
Resistance to Acid	No
Resistance to Alkali	Yes
Resistance to UV	Yes
Resistance to Heat	^240°C
Extension at 50%	13%
Extension at break	35%

FEATURES & BENEFITS

- 8-strand Nylon construction
- Torque neutral
- Longer rope constructional pitch
- High extension under load
- Easy to handle long lengths
- Low “noise” when under load
- Can be spliced directly to chain

TYPICAL APPLICATIONS

- Anchor wraps
- Mooring wraps

