








BRAID-ON-BRAID

LEISURE MARINE • COMMERCIAL MARINE • SUB SEA • RENEWABLE ENERGY •
ARBORIST • THEATRE & EVENTS • UTILITIES • WINCHING • DEFENCE

This 100% Polyester range of ropes designed for sheet and halyard use has superb durability and continues to be the first choice for cruising yachtsmen.

Reference	Diameter (mm)	Reel Length (m)	Weight (kg/100m)	Breaking Load (kg)	Breaking Load - Spliced (kg)		960/ Red fleck†	910/ Blue fleck†	980/ Yellow fleck	928/ Green fleck
1606	6	200	2.9	1,350	1030		16060200960	16060200910	16060200980	16060200928
1608	8	200	5.1	2,000	1600		16080200960	16080200910	16080200980	16080200928
1610	10	200	7.6	3,150	2520		16100200960	16100200910	16100200980	16100200928
1612	12	100	11.7	4,300	3440		16120100960	16120100910	16120100980	16120100928
1614	14	100	15.6	6,000	4820		16140100960	16140100910	16140100980	16140100928
1616	16	100	19.5	7,250	5800		16160100960	16160100910	-	16160100928
1618	18	100	23.4	7,500	6000		16180100960	16180100910	-	16180100928
1620	20	100	34.0	11,000	8800		16200100960	16200100910	-	-
1624	24	100	40.4	14,000	11200		16240100960	-	-	-

Reference	Diameter (mm)	Reel Length (m)	Weight (kg/100m)	Breaking Load (kg)	Breaking Load - Spliced (kg)		000/ White†	912/ Navy	900/ Black	994/ Beige
1606	6	200	2.9	1,350	1030		16060200000	16060200912	16060200900	16060200994
1608	8	200	5.1	2,000	1600		16080200000	16080200912	16080200900	16080200994
1610	10	200	7.6	3,150	2520		16100200000	16100200912	16100200900	16100200994
1612	12	100	11.7	4,300	3440		16120100000	16120100912	16120100900	16120100994
1614	14	100	15.6	6,000	4820		16140100000	16140100912	16140100900	16140100994
1616	16	100	19.5	7,250	5800		16160100000	16160100912	16160100900	16160100994
1618	18	100	23.4	7,500	6000		16180100000	16180100912	16180100900	16180100994
1620	20	100	34.0	11,000	8800		16200100000	-	16200100900	16200100994
1624	24	100	40.4	14,000	11200		16240100000	-	-	-

Pre-stretched, non-kinking and flexible in all conditions, Braid-On-Braid is easily spliced and works well with deck hardware. Braid-On-Braid is available in a full range of white with flecks or a range of vibrant solid colours.

TECHNICAL INFORMATION

	Core	Cover
Construction	12-strand	24-plait
Material	polyester	polyester
Specific gravity	1.38	1.38
Resistance to acid	yes	yes
Resistance to alkali	yes	yes
Resistance to UV	yes	yes
Resistance to heat	~230°C	~230°C
Extension at 50%	5%	

FEATURES & BENEFITS

- Double braid construction
- Full colour range available
- Easily spliced
- Superior wear resistance and longevity
- Ease of identification through colour range
- Perfectly balanced and easy to handle
- Heat set and pre-stretched

TYPICAL APPLICATIONS

- Leisure Marine - Halyards, Sheets
- Industrial Winching
- Arborist Rigging Lines

