

D-TRACT

COMMERCIAL MARINE • SUB SEA • RENEWABLE ENERGY •
HEAVY LIFTING • UTILITIES • WINCHING • DEFENCE

A replacement for traditional wire solutions.

Reference	Diameter (mm)	Weight (/100m)	Minimum Breaking Load - Spliced (t)	903/ Grey
5809	9	3.8	6.80	58090100903
5810	10	4.6	8.00	58100100903
5811	11	5.7	10.60	58110100903
5812	12	6.6	12.10	58120100903
5814	14	8.6	14.20	58140100903
5816	16	9.4	16.20	58160100903

Our D-Tract rope range is a development from our 12-Strand Dyneema® product to meet the demands of the winching market. This involves optimising the pitch to protect the rope from dirt ingress which in effect increases the lifespan of the product. Available in finished assemblies.

FEATURES & BENEFITS

- 12-strand construction
- Protective coating
- Colour coated on request
- Lightweight high tenacity
- Torsionally stable
- Reduced manpower requirements
- Spliced custom lengths

TYPICAL APPLICATIONS

- 4x4 winching
- Vehicle recovery

TECHNICAL INFORMATION

	Core	Cover
Construction	12-strand	-
Material	Dyneema®	-
Specific gravity	0.97	-
Resistance to acid	Very good	-
Resistance to alkali	Very good	-
Resistance to UV	Very good	-
Resistance to heat	Poor	-
Extension at 50%	xxx	-
Extension at break	xxx	-

 **Dyneema®**