

DINGHY DYNEEMA®

SAILING • LEISURE MARINE • PERFORMANCE • DEFENCE • TECHNICAL CORDS

Featuring a 32-plait polyester cover, Dinghy Dyneema® performs well in hardware without getting damaged.

Reference	Diameter (mm)	Reel Length (m)	Weight (/100m)	Breaking Load (kg)	000/ White	960/ Red	910/ Blue	982/ Neon
5401	1	200	0.1	50	54010200000	-	-	-
5415	1.5	200	0.15	70	-	-	-	-
5402	2	200	0.3	120	54020200000	54020200960	-	54020200982
5403	3	200	0.6	370	54030200000	54030200960	54030200910	54030200982
5404	4	200	1.1	996	54040200000	54040200960	54040200910	54040200982
5405	5	200	1.7	1,200	54050200000	54050200960	54050200910	54050200982
5406	6	200	2.5	1,910	54060200000	54060200960	54060200910	54060200982

Reference	Diameter (mm)	Reel Length (m)	Weight (/100m)	Breaking Load (kg)	900/ Black & yellow	902/ Black & white
5401	1	200	0.1	50	-	-
5415	1.5	200	0.15	70	-	54150200902
5402	2	200	0.3	120	-	-
5403	3	200	0.6	370	54030200900	-
5404	4	200	1.1	996	54040200900	-
5405	5	200	1.7	1,200	54050200900	-
5406	6	200	2.5	1,910	54060200900	-

The Dyneema® core is protected by a tightly woven polyester jacket providing good abrasion resistance with the strength being delivered through the Dyneema® SK78 core material. This product is ideal for Dinghy halyards which require a performance line through high strength and low creep attributes.

FEATURES & BENEFITS

- Dyneema® SK78 core
- Bright colour scheme and colour matching core
- 32-plait 'one over one under one'
- High strength with low extension
- Improved longevity with Dyneema® SK78
- Hard wearing cover

TYPICAL APPLICATIONS

- Dinghy control line
- Dinghy halyards
- Dinghy sheet ropes

TECHNICAL INFORMATION

	CORE	COVER
Construction	12 Strand	32 Plait
Material	Dyneema®	Polyester
Specific Gravity	0.97	1.38
Resistance to Acid	Yes	Yes
Resistance to Alkali	Yes	Yes
Resistance to UV	Yes	Yes
Resistance to Heat	~150 C	~230 C
Extension at Break	3.5%	



Dyneema®

