

DOCKLINE

LEISURE MARINE

Our premium mooring product designed to be hard wearing in even the toughest environments while remaining flexible for ease of handling.

Reference	Diameter (mm)	Reel Length (m)	Weight (/100m)	Breaking Load (kg)	900/ Black†	912/ Navy	904/ Reflective
1312	12	200	11.4	3,200	13120200900	13120200912	13120200904
1314	14	200	15.6	4,620	13140200900	13140200912	13140200904
1316	16	100	19.5	6,080	13160100900	13160100912	13160100904
1318	18	100	23.4	7,300	13180100900	13180100912	-
1320	20	100	33.5	8,600	13200100900	13200100912	-

Although a double braid the rope is designed to a differing specification it delivers a softer easier to handle line consistent with the docking operations. Manufactured from high tenacity polyester. Very simple to splice and with a soft feel, these distinctive mooring lines stay soft and strong in all environments and represent exceptional value for strength and durability.

TECHNICAL INFORMATION

	Core	Cover
Construction	16 plait	24 plait
Material	Polyester	Polyester
Specific Gravity	1.38	1.38
Resistance to Acid	Yes	Yes
Resistance to Alkali	Yes	Yes
Resistance to UV	Yes	Yes
Resistance to Heat	^230 C	^230 C
Extension at 50%	8%	

FEATURES & BENEFITS

- Double braid construction
- Soft feel
- Heat set
- Easy to handle and store
- Easy to splice
- Holds a knot well
- High tenacity

TYPICAL APPLICATIONS

- Mooring lines

