

 *MADE TO ORDER

ELITE DC75/78 & DC75/78XPS

LEISURE MARINE • CRUISING • RACING • SUPERYACHT

A lightweight and high strength, single braid Dyneema® core.

Core Diameter (mm)	Finished Rope Diameter (mm)	Min Order (m)	Weight (kg/100m)		Average Strength (Spliced, kg)		Minimum Strength (Spliced, kg)	
			DC75/78	DC75/78XPS	DC75/78	DC75/78XPS	DC75/78	DC75/78XPS
2.5	3	100	0.37	-	569	-	490	-
3	4	100	0.53	-	995	-	855	-
3.5	5	100	0.74	-	1430	-	1070	-
5	7	100	1.28	-	2360	-	2120	-
6	8	100	1.77	2.23	3490	4570	3140	4250
7	10	100	2.80	3.74	5360	7510	4930	6980
9	12	100	3.76	5.40	6940	10800	6250	10000
10	14	100	4.83	6.30	9270	12600	8530	11700
11	16	100	5.82	7.55	11600	15100	10700	14100
13*	18	100	8.00	10.70	15900	21100	14300	19700
15*	20	100	9.80	13.40	18400	26400	16600	23700
16*	22	100	11.80	-	21100	-	19000	-
17*	-	100	-	18.40	-	32900	-	30600
18*	24	100	14.30	-	25200	-	22600	-
19*	26	100	15.70	-	27500	-	23700	-
20*	28	100	18.00	-	33500	-	29000	-

Ideal for applications such as control lines, cores for halyards, dinghy standing rigging, guys and runners.

Without a cover it can be used as a trip line, lashing, sheet, strop, tack line or wire replacement. Stock colour is grey, other colours available on request.

FEATURES & BENEFITS

- Easily inspected, repaired and spliced
- Excellent abrasion resistance
- Floats (no water absorption)
- Good chemical resistance
- Good UV resistance
- High strength
- Low creep
- Low elongation
- Minimal recoil
- Reduced diameters
- Very light weight
- Zero water shrinkage

TYPICAL APPLICATIONS

- Control line
- Cores for halyards
- Dinghy standard rigging



Sustainable/Eco-Friendly
options available.