

RIG-TEX 24

ARBORIST

Premium quality double braid construction

Reference	Diameter (mm)	Reel Length (m)	Weight (kg)	Minimum Breaking Load - Spliced (kg)	970/ Red	984/ Orange	971/ Blue	975/ Yellow
1610R	10	200	7.6	3,150	1610R0200970	-	-	-
1612R	12	200	11.7	4,300	-	1612R0200984	-	-
1614R	14	200	15.6	6,000	-	-	1614R0200971	-
1616R	16	100	19.5	7,250	-	-	-	1616R0100975
1618R	18	100	23.4	7,500	-	-	-	-
1620R	20	100	34.0	11,000	-	-	-	-

Reference	Diameter (mm)	Reel Length (m)	Weight (kg)	Minimum Breaking Load - Spliced (kg)	974/ Green	968/ Pink
1610R	10	200	7.6	3,150	-	-
1612R	12	200	11.7	4,300	-	-
1614R	14	200	15.6	6,000	-	-
1616R	16	100	19.5	7,250	-	-
1618R	18	100	23.4	7,500	1618R0100974	-
1620R	20	100	34.0	11,000	-	1620R0100968

A heat set and pre-stretched polyester rope suitable for a wide range of application. Used widely in yachting, industrial winching and arboriculture.

FEATURES & BENEFITS

- Double braid construction
- 12-strand core, 24 Plait cover
- Full colour range available
- Heat set and pre-stretched
- Easily spliced
- Superior wear resistance and longevity
- Ease of identification through colour range
- Perfectly balanced and easy to handle

TYPICAL APPLICATIONS

- Arborist rigging

TECHNICAL INFORMATION

	Core	Cover
Construction	12-strand	24-plait
Material	Polyester	Polyester
Specific gravity	1.38	1.38
Resistance to acid	Yes	Yes
Resistance to alkali	Yes	Yes
Resistance to UV	Yes	Yes
Resistance to heat	^230°C	^230°C
Extension at 50%	5%	